

Adapt-IQ 7" Digital Signage Tablet

Model: MCT-70HPQ



A truly brilliant, smart, and professional Android tablet designed for commercial and retail use.

The Adapt-IQ by Mimo is not a consumer tablet, but a tablet thoughtfully designed for commercial use where running 24/7 is crucial. With hardware designed for commercial and retail use, added features such as robust case, tempered glass, design and testing for 24/7 use, VESA mounting (75mm x 50mm), SD card protection system, stereo audio output, our tablet is the best Android solution for the demanding commercial and retail environment. The Adapt-IQ utilizes the security of wired with optional power over Ethernet OR the convenience of wireless Ethernet connections. Designed for fixed applications where a rugged mountable Android tablet is desired and where battery power is not required.

The Mimo Adapt-IQ tablet is designed to enhance the customer experience and provide the most cost effective solutions for retail POS/POP, commercial, industrial, and hospitality markets. Perfect for end-cap displays, kiosks, or as a customer-facing display in retail POS/POP environments.

Build for long term use and support

The Adapt-IQ is designed and supported as a long term commercial product. The external specifications and tooling are controlled to ensure a long product life, which is crucial for maintaining continuity for all phases of project rollouts and service. The internal assemblies were developed for the Adapt-IQ and are not subject to obsolescence. While internal components may change for the better, this can be done without modification by the end user.

Quad Core ARM A17

The Mimo Adapt-IQV 10-inch Android-powered signage player uses a quad core Cortex A17 chipset with a 1.8GHz peak frequency that supports the latest ARM processor optimized package. Apps launch instantly and run smoothly. The processor features a quad-core GPU, so that all graphic-intensive apps are fluid and lifelike. All this, combined with 2GB of dual-channel DDR3 memory, distinguishes our tablet from other solutions.

Android 8.1 Oreo OS, license free

The quad-core Adapt-IQ with Android 8.1OS has blazing fast loading times. Accelerated webpage speed by 50%, video/photo loading speed by 30%, app installation speed by 25%, and app loading speed by 16%. To meet customized needs, the Adapt-IQ by Mimo can be installed with applications downloaded from Android Market. Improved memory usage across the platform to ensure that apps can run efficiently on devices with 1GB or less RAM.



High-quality tempered glass multi-touch panel

The Adapt-IQ by Mimo features a 5 point multi-touch projected capacitive panel. The capacitive touch panel is made of scratch-free tempered glass, and produced with a double- deck glass process and advanced laser carving. The touch panel responds fast and accurately without dead corners, allowing users to easily interact with your designed app.

VESA mount and wired Ethernet

Unlike consumer tablets, the Adapt-IQ is designed with VESA mounting (75mm x 50mm) holes on the back, and an SD card with protection cap to meet the demanding environment of commercial and retail installations. In addition to the built-in Wi-Fi, our tablet comes with a wired RJ45 Ethernet connection and a SD memory slot to expand the internal memory. On the Adapt-IQ, you can also connect printers, bar code scanners, or any other USB accessory to the USB ports located on the back side tablet.

Add on Module Slot

The Adapt-IQ by Mimo has 1 USB based add on module slot. This slot is designed to accept a magnetic stripe reader 2D barcode reader, NFC module and more. New hardware capabilities can be added for future requirements.

Play Full HD video smoothly, support, Flash & HTML5

The Adapt-IQ by Mimo plays full HD 1080P videos smoothly, and is compatible with 480P and 720P videos in all kinds of formats: TS, H.264, WMV, MPEG4, etc. The tablet supports Adobe Flash 11.0 and HTML5 animation technology, and can easily access dynamic webpage, and on-line videos or games.

The best equipped commercial and retail tablet

The Adapt-IQ is fully equipped with all the typical tablet functions for running advanced and sophisticated client applications and offering users a rich and interactive experience.

Elegant, Light, Durable, Modern, Professional

The Adapt-IQ 7" is designed with high-quality ABS case with modern zero-bezel design, thus greatly improving scratch resistance.

Technical Specifications

	TFT LCD	7" inch configuration
Display	Number of Pixel	1024 x 600
	Aspect Ratio	16:9 wide
	Touch Panel	5 point touch projected capacitive
	Back-light	LED Side-light type
	Brightness	250 cd/m2
	Contrast Ratio	700:1
Media Format	Video	MKV, TS, FLV, AVI, VOB, MPG, DAT, ASF, RM, MOV, 3GP, MP4, WMV
	Audio	MP2, WMA, WAV, AAC, OGG, ASF
	Picture	JPG, BMP, GIF
1/0	SD card slot	SD card (SDHC Class10 compatible)
	USB	USB 2.0 host type A×1
	Micro USB	Micro USB 2.0 × 1
	Add-on Module slot	USB 2.0 x 1
Speakers	High quality speaker	1W x2
	Amplifier	1W x2
Power	Power requirement	DC 5V±5% input – barrel connector
	Power consumption	1KHz audio playback: ~7.5W max Off: 0W
	AC/DC Adapter	AC 100-240Vac, 2A max. 50-60Hz, 5V/1.5A AC/DC Adapter supplied
	Power over Ethernet POE	No
	LED	ON: Green - Timer standby: Orange - OFF: light off
	Switch	Power switch on back
Ethernet	RJ45	10/100Mbps LAN
Wireless	Wi-Fi	802.11 b/g/n
	Bluetooth	BT4.0
Camera	Front	Front: 5M pixels (optional)
Function Keys	Keys button	+, -, Up, Down, Menu/Enter
Barcode Scanner	Barcode Scanner	2D Barcode scanner (optional)
Hardware Systems	СРИ	Cortex-A9, Quad Core, up to 1.6 GHz
	DRAM Memory	2GB DDR3 SDRAM
	Storage Memory	8GB eMMC Flash
	External Memory	SD Card (SDHC Class10 compatible)
	Software / OS	Android 8.1 Oreo
	Flash	Adobe 10.2 supported
General Information	Case design	Body and cover are black ABS & PC
	Dimensions without add-ons	Width: 207mm x Height: 120mm x Depth: 23mm
	Weight without add-ons	450q
	Mounting	VESA 75mmx75mm mounting screw holes
	Clock Battery (for RTC)	Lithium-ion non-rechargeable coin battery
	Storage Temp	-15 65 degrees C
		-1050 degrees C
	Working Temp	
	Storage / Working Humidity	10 – 90% non-condensing
	MTBF	30,000 hours demonstrated
	Warranty	3 years
	Certifications	FCC, CE, & RoHS



Mechanical Design

Front

1. Camera (optional)



Top 2. LED

- SD card slot + cover
- Menu/Enter button
- Function keys (up/down)
- Function keys (Vol+ / Vol-)



Back

- 7. Speakers
- 8. VESA mounting holes 75mm x 50mm
- 10. Add on Module Slot



Bottom

- 9. DC in
- 10. Add on Module Slot
- 11. Ethernet RJ45 port
- 12. USB type A
- 13. Micro USB
- 14. Power switch

Mimo Monitors

743 Alexander Rd. Suite 15 Princeton, NJ 08540

info@mimomonitors.com

Sales: 1-855-YES-MIMO (937-6466)