



Outdoor Touch or Non-Touch, IP65 Rated, High Bright Display, with Audio, HDMI, Android 14

MOT Series. See Part Numbers, Screen Sizes and Specifications on the next page



Mimo Outdoor Displays

Durable, reliable, and exceptionally bright, the refreshed line of Mimo Outdoor Displays are engineered for demanding year-round outdoor use across a wide operating temperature range. Designed to withstand harsh environments, the IP65-rated enclosure protects against water, dust, moisture, sand, and insects, while rugged construction and enhanced sealing ensure long-term performance. Its high-brightness output delivers clear, crisp visuals in direct sunlight and ambient lighting, making content easy to see at all times. Manufactured in TAA-compliant facilities and backed by an industry leading three-year standard warranty, Mimo Outdoor Displays provide dependable, high-impact digital signage for applications including QSR drive-thrus, outdoor kiosks, transportation hubs, retail storefronts, stadiums, and other high-exposure commercial environments.

Notable Features:

- IP65 outdoor rating
- Optically bonded to reduce glare
- High bright, vivid screen
- Wide operating temperature for very hot and very cold conditions

Applications:

- Outdoor digital signage
- Outdoor wayfinding
- Outdoor menu boards with ordering capability
- Outdoor stadiums and amusement parks
- Outdoor restaurants and food trucks
- Outdoor transportation
- Outdoor service and gas stations



Available Screens, Sizes & Options

MOT Series (Android OS)	CH PCAP touch
MOT-10181H	
MOT-10181CH	x
MOT-21581H	
MOT-21581CH	x
MOT-32081H	
MOT-32081CH	x

MOD Series (No OS)	CH PCAP touch
MOD-10181H	
MOD-10181CH	x
MOD-21581H	
MOD-21581CH	x
MOD-32081H	
MOD-32081CH	x

Mimo Part Number Example:

MOT-10181H = a 10.1" non-Touch tablet
MOD-21581CH = 21.5" PCap touch display

Product Specifications

Display Size	10.1"	21.5"	32"
Overall Dimensions (mm)	266 x 188 x 58	543 x 334 x 72	761 x 456 x 93
Weight	4.76lbs / 2.04kg	16.04lbs / 5.36kg	34.84lbs / 5.36kg
Resolution	1280 x 800	1920 x 1080	1920 x 1080
Brightness (pre-touch)	1200nits	1400nits	1600nits
Contrast Ratio	800:1	1000:1	5000:1
CG Hardness	IK08		
Processor (MOT only)	RK3576		
WiFi (MOT only)	2T2R 802.11 ax/ac/a/b/g/n		
Ethernet Controller (MOT only)	Dual Ethernet 10/100/1000M		
Connections	• USB A Media & Keyboard & mouse • RJ 45 internet • HDMI signal Out • DC Jack Power In • Air Vents • Power Key		
Viewing Angle	89/89/89/89		
Operating Environment	Temp: -10°C~50°C Humidity: 20-90%		
Power Consumption (max / TYP)	23/10 W	64/54 W	112/98 W
VESA Mount Pattern	100x100mm	100x100mm	200x200mm
Enclosure Material	Aluminum		
Touch Panel Interface	USB		
I/O Port	RJ45*1,HDMI*1,USB*1		
OS (MOT only)	Android 14		
Regulatory Certifications	FCC, CE, ROHS, TAA Compliant		